



A tool to light.

The luminaire is pure form, a simple container for the light source.  
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.  
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Indoor

**Material** Metal  
**Finish** .03 Matt White .04 Matt Black

**Note** Recessed luminaire. Adjustable in all directions. Plasterboard hole: 133x148 mm. Minimum space for recessed installation: 180 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 133x148 mm. Spazio minimo per incasso: 180 mm.*



**PUNTO**

Max 21W  
 Max 500mA DC  
 CRI >90  
 Driver not included  
 LED module not included



Matt White  
 Matt Black

1A1100300.00.20  
 1A1100400.00.20

**Compulsory accessories / Accessori obbligatori**

Installation kits / Kit d'installazione



Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm		Not included
Matt White	Cut-out 133x148 mm Minimum space for mounting 180 mm	1A3510300.00.00
Matt Black	Cut-out 133x148 mm Minimum space for mounting 180 mm	1A3510400.00.00

LED modules / Moduli LED



DG111 LED module / Modulo LED DG111		Not included
16,7W - 15° - 500mA DC	2700K - 1648lm - CRI >90 Energy Efficiency F - Dimmable	1A4700000.27.20
16,7W - 15° - 500mA DC	3000K - 1682lm - CRI >90 Energy Efficiency F - Dimmable	1A4700000.30.20




DG111 LED module / Modulo LED DG111		Not included
16,7W - 22° - 500mA DC	2700K - 1859lm - CRI >90 Energy Efficiency F - Dimmable	1A3890000.27.20
16,7W - 22° - 500mA DC	3000K - 1945lm - CRI >90 Energy Efficiency F - Dimmable	1A3890000.30.20




DG111 LED module / Modulo LED DG111		Not included
16,7W - 36° - 500mA DC	2700K - 1808lm - CRI >90 Energy Efficiency F - Dimmable	1A3900000.27.20
16,7W - 36° - 500mA DC	3000K - 1890lm - CRI >90 Energy Efficiency F - Dimmable	1A3900000.30.20


Drivers / Alimentatori



Driver / Alimentatore		Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/DALI	1Z0241180.500



Driver / Alimentatore		Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH	1Z0240840.500



Driver / Alimentatore		Not included
220-240V	500mA/20W/IP20/TRIAC/IGBT	1Z0240850.500

**Optional accessories / Accessori opzionali**

Other accessories / Altri accessori



**Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluca nido d'ape** Not included  
 Matt Black 1X0070400.04.00



**Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico** Not included  
 Matt Black 1X0070400.05.00



**Blue filter / Filtro blu** Not included  
 Standard Compulsory with 1X0070000.06.00  
 1X0070400.04.00 / 1X0070400.05.00



**Red filter / Filtro rosso** Not included  
 Standard Compulsory with 1X0070000.07.00  
 1X0070400.04.00 / 1X0070400.05.00



**Yellow filter / Filtro giallo** Not included  
 Standard Compulsory with 1X0070000.08.00  
 1X0070400.04.00 / 1X0070400.05.00

